



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS

Size (sq.mm.)	FR					
	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75	770	28			2570	10
1	1005	24	2010	12	3350	8
1.5	1490	16	2980	10	4965	6
2.5	2400	12	4800	6	8000	4
4	3550	8	7100	4	7890	4
6	5265	6	10530	3	11700	3
10	9265	1			20590	1
16	14830	1			32955	1

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LOW SMOKE (FRLSH) /FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 VOLTS

Size (sq.mm.)	FRLS				FRZH/LSZH/HFFR	
	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75			2710	10	3030	10
1	2075	12	3460	8	3745	8
1.5	3140	10	5235	6	5800	6
2.5	5055	6	8425	4	9545	4
4	7465	4	8295	4	9265	4
6	11025	3	12250	3	13535	3
10			21690	1	23825	1
16			34760	1	38000	1

Notes

1. Excise Duty, VAT, Entry Tax, Octroi/ LBT and any other tax/levy will be charged extra, as per actuals.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB INDUSTRIAL JELLY FLOODED COAXIAL CABLES

Polycab Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.

Size	100m Unarmoured	305m Unarmoured	1000m Armoured
RG - 59	1825	5565	74150
RG - 6	2370	7225	77000
RG - 11	4915	15020	118830
RG-6 CCS	1505	4595	69400
RG-11 CCS	3015	9185	

POLYCAB LAN (COMPUTER) CABLES

Polycab 4 Pair Unshielded Twisted Pair (UTP) LAN (Computer) Cables

Polycab 4 Pair Shielded Twisted Pair (STP) LAN (Computer) Cables

	Unarmoured Rate per 305 m	Armoured- Rate per 100m	STP- Rate per 305m	Armoured – Rate per 100m
CAT 5 E	8515	6640	11040	7895
CAT 6	10155	7610	12875	9035



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB INDUSTRIAL TELEPHONE (SWITCHBOARD)CABLES

Polycab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification

No. of Pairs & Size			
	0.4 mm	0.5 mm	Master Packing
1 Pair	634	760	20
2 Pair	1009	1330	20
3 Pair	1482	1940	16
4 Pair	1901	2550	12
5 Pair	2379	3185	8
10 Pair		6085	1
20 Pair		11700	1
50 Pair		32370	1
100 Pair		61815	1

ARMoured TELEPHONE CABLES

No. of Pairs	Rate / 100m (0.5sqmm)	Master Packing
2 Pair	4375	Drums/Coils as required
5 Pair	7215	Drums/Coils as required
10 Pair	10800	Drums/Coils as required
15 Pair	14800	Drums/Coils as required
20 Pair	18200	Drums/Coils as required
50 Pair	43800	Drums/Coils as required
100 Pair	80100	Drums/Coils as required

POLYCAB IND. 3C FLAT SUBMERSIBLE CABLES

Polycab PVC Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade upto 1100 Volts as per IS:694/1990

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Cables (No./dia mm)	Rate per 100m (Rs)
1.5	22/.3	6200
2.5	36/.3	9600
4	56/.3	14100

Polycab Special PVC Insulated & PVC Sheathed Industrial 3 Core Flat Submersible Cables with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade Upto 1100 Volts generally conforming to IS 694/1990.

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Cables (No./dia mm)	Rate per 100m (Rs)
6	84/0.3	20900
10	80/0.4	35600
16	126/0.4	58400
25	196/0.4	93500
35	276/.4	131000
50	396/.4	187500
70	354/.5	260900
95		337200
120		431000
150		537100

Notes :

1) The above cables are supplied in 500/1000m drums.

2) Polycab Three Core Flat Submersible Cables

Insulated & Sheathed with XLPE can be supplied at

the same rates as given above.



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

Polycab PVC Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade upto 1100 Volts as per IS: 694:1990

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)							
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	595	25	1870	2520	3240	4	4220	5000
0.75	24/.2	8	840	25	2495	3395	4220	4	5900	7225
1	32/.2	13	1090	20	2975	4100	5350	4	7800	9100
1.5	30/.25	17	1590	16	4030	5650	7500	4	10100	12400
2.5	50/.25	24	2610	12	6415	9050	12000	3	16700	20200
4	56/.3	30	4100	8	9500	13500	17700	1	25400	32000
6	84/.3	38	5950	6	14200	20600	26700	--	39300	47000
10	80/.4	52	10300	1	24300	35000	45500	--	66800	--
16	126/.4	70	16700	1	38700	55700	73300	--	104100	--
25	196/.4	88	26200	1	75100	102100	134300	--	176600	--
35	276/.4	110	36300	1	102500	141400	185600	--	243900	--
50	396/.4	145	51700	1	148400	201400	269600	--	353500	--
70	354/.5	215	71900	1	211400	289700	376600		493200	
95	484/.5	260	100600	1	285500	396900	524100		680600	
120	608/.5	305	128300	1	361400	503700	675700		883900	
150	750/.5	355	160600	1	451000	625800	826500		1082800	
185	925/.5	415	197800	1	556100	760200	1007700		1321500	
240	1210/.5	500	257200	1	721900	1003200	1325700		1741100	
300	1527/.5	585	320900	1	902300	1251000	1658300		2165400	
400	2036/.5	695	436500	1	1203000	1647000	2183100		2872600	

FR Insulation :	5%
FRLSH /HR Insulation :	10%
HFFR :	25%



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	5770	6730	8400	9750
0.75	24/.2	8	7800	9650	11800	13800
1	32/.2	13	10500	12200	14800	17600
1.5	30/.25	17	14200	16400	20500	24400
2.5	50/.25	24	23100	26900	33300	39900
4	56/.3	30	41100	47000	59900	73400
6	84/0.3	37	54800			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	11400	12800	15000	19100
0.75	24/.2	8	16100	18600	21500	27300
1	32/.2	13	20700	23300	27900	35000
1.5	30/.25	17	28400	32000	38000	47800
2.5	50/.25	24	46000	52900	61700	77500

Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables				Rate/ 100m	CCTV CABLES Rate/90m	
Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armouring Cables	CCTV Cables 4+1	CCTV Cables 3+1
mm ²	No/mm		Rs	Rs	3900	3425
4	56/0.3	44				
6	84/0.3	55	7605	10457		
10	80/0.4	75	12929	17872		
16	126/0.4	103	19678	22815		
25	196/0.4	126	30705	34983		
35	276/0.4	152	42018	46961		
50	396/0.4	189	59034	65118		
70	354/0.5	240	81374	89549		
95	484/0.5	297	110082	114836		
120	608/0.5	346	139076	145256		
150	750/0.5	390	173869	181569		
185	925/0.5	460	212180	218739		
240	1210/0.5	552	275586	288705		
300	1527/0.5	640	343841	363139		
400	2036/0.5	753	458486	481206		
500	2530/0.5	865				
630	3180/0.5	1001				



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:1990 with Flexible Bright Annealed Copper Conductor for Voltage Grade upto 1100 Volts

Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade upto 1100 Volts as per IS: 694:1990

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Single Core (Rate/100m)	(Rate/100m)		
				Two Core	Three Core	Four Core
0.5	16/.2	5	619	1950	2711	3447
0.75	24/.2	8	868	2623	3637	4729
1	32/.2	13	1141	3227	4495	5874
1.5	30/.25	17	1648	4280	6006	8034
2.5	50/.25	24	2711	6840	9604	12675
4	56/.3	30	4305	10238	14625	19305
6	84/.3	38	6118	15405	21938	29055
10	80/.4	52	10530	25935	37635	49530
16	126/.4	70	17160	40950	59475	78390
25	196/.4	88	27300	80400	111000	146000
35	276/.4	110	37538	109300	153700	201700
50	396/.4	145	53625	158600	218800	292900
70	354/.5	215	74490	225900	314600	409000
95	484/.5	260	104228			
120	608/.5	305	132893			
150	750/.5	355	166140			
185	925/.5	415	204750			
240	1210/.5	500	265980			
300	1527/.5	585	332378			
400	2036/.5	695	451913			



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB SOLAR WIRES / CABLES

Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing , Heat Resistant upto 120°C and UV Resistant Solar Cables		Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulated and UV Stabilized PVC Sheathed Single Core and Multicore Solar Cables	
Size in sq mm	Rate Per 100m	Size in sq mm	Rate Per 100m
1.5	4750	1.5	2750
2.5	6500	2.5	4400
4	9300	4	6700
6	12500	6	9600
10	19700	10	16500
16	29100	16	24800
25	45100	25	38500
35	61400	35	53300
50	88000	50	76600
70	121900	70	106400
95	154800	95	144800
		120	179800
		150	223400
		185	285000
		2 C x 16	54500
		2 C x 25	84100

POLYCAB BUILDING MANAGEMENT SYSTEM CABLE (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
2	3846	4569	5478	6590	11030
3	4569	5682	6896	8814	13254
4	5682	6998	8629	11215	17240
5	6488	8101	10381	13161	20669
6	7304	9732	11956	15386	25767
7	8119	10937	13439	17703	28084
10	11400	14830	18723	24840	39762
12	13161	17518	21967	29196	47177
14	15108	19927	25396	33830	54129
16	17054	22986	27806	37909	62285
19	19557	26230	33460	44860	72295
24	24376	31884	41987	56816	91296

Note : 3% Extra Charges for Drum Packing



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB INDUSTRIAL BRAIDED CABLES

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)

Cores	7/36	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)	4 sq.mm. (56/.3)	6 sq mm (84/.3)	10 sq.mm	16 sq.mm	25 sq mm	35 sq.mm.	50 sq.mm.
2	4249	5295	6806	7557	9696	13404	20058	25762	50408	78390			
3	5295	6521	8318	8879	11788	17587	25952	33367	63083	98670	132990	184470	241313
4	6521	8223	10172	11312	14735	23005	30610	48387	90090	144105	193050	244530	347490
5	7938	9791	13594	15305	18157	27473							
6	8983	11312	14640	16161	22055	33082							
7	9696	12073	15875	17872	23671	38215							
8	11598	14354	18727	19488	27093	43253							
10	13784	17206	23005	25667	34318	50288							
12	15685	19773	25762	28614	40021	56087							
14	17206	21484	29469	30705	46866	65213							
16	19868	24906	32511	37360	51524	75004							
19	22815	28519	38025	44014	61220	103048							
24	28329	35268	45155	55136	75575	125387							



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)

Flex Bare Copper Conductor, PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	2 Core	3 Core	4 Core	Core	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
1.5	30/.25	8663	11449	14821	5	17705	27231
2.5	50/.25	12898	17325	22137	6	20496	31855
4	56/.3	18667	25022	32718	7	23385	36573
6	84/.3	26269	35706	46193	8	26368	40222
10	80/.4	38683	53608	71120	9	29069	44654
16	126/.4	58509	81903	107403	10	31761	49565
25	196/.4	88446	125310	165729	12	37150	58420
35	276/.4	121262	172558	227324	15	45714	72467
50	396/.4	170344	243871	322504	16	48402	76993
70	354/.5	255999	368604	488708	18	53894	85655
95	484/.5	345505	498243	661941	19	57458	89886
120	608/.5	430194	621714	826127	21	62654	98844
150	750/.5	536640	776468	1031023	24	70834	111915
185	925/.5	667813	957018	1269697			
240	1210/.5	854333	1239296	1646875			
300	1527/.5	1065866	1547646	2058491			

Note : 3% Extra Charges for Drum Packing

Polycab Industrial Speaker Wires

Speaker Wires (Oxygen Free) (Rate per 90 mtr)

Size 23/36	Size 40/36	Size 70/36
1685	2670	4660
Size 23/38	Size 40/38	Size 70/38
1200	1990	3130

** Flame Retardant, Heat Resistant up to 90°C & Oil Resistant

POLYCAB INDUSTRIAL WELDING CABLES

Polycab Flexible Copper Conductor Welding Cable upto 1100 Volts as per IS-9857 (Rate per 100 mtr)

Nominal Area of Conductor (sq mm)	Current Carrying Capacity	Conductor Constn. Strands/ Dia in mm	TPR Insulation Rate/100m (Rs)
16	120	509/0.2	22600
25	160	796/0.2	32500
35	230	1115/0.2	44300
50	400	703/0.3	62700
70	600	999/0.3	89500
95	700	1346/0.3	118100
120	1100	1699/0.3	151500



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB ALUMINIUM WIRES & CABLES

POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>SOLID</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>STRANDED</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694		
SQ.MM	RATE/ 100M	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/ 100M
1.5	424	1.5	424	2	1.5	1584
2.5	666	2.5	666	2	2.5	2240
4	868	4	979	2	4	3158
6	1311	6	1352	2	6	4136
10	1957	10	2028	2	10	6406
POLYCAB <u>SINGLE CORE</u> PVC INSULATED & <u>SHEATHED</u> 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		16	2915	2	16	8494
		25	4550	2	25	11985
		35	6123	2	35	15364
		50	8262	2	50	19611
SQ.MM	RATE/ 100M	70	11006	2	1.5	2179
1.5	646	95	12852	3	2.5	3158
2.5	797	120	18633	3	4	4469
4	1523	150	23102	3	6	6214
6	2068	185	28761	3	10	9150
10	2835	240	37366	3	16	12418
16	4035	300	46627	3	25	17432
25	5881	400	59923	3	35	22557
35	7516	500	76265	3	50	28761
50	9967	630	96532	POLYCAB <u>XLPE</u> INSULATED AND <u>PVC</u> SHEATHED CABLE WITH EACH CORE HAVING STRANDED ALUMINIUM CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694.		
POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>SOLID</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694				NO.OF CORES	SQ.MM	RATE/100M
NO.OF CORES	SQ.MM		RATE/ 100M	2	4	2915
2	1.5		1463	2	6	4146
2	2.5		2139	2	10	5165
2	4		2915	2	16	7516
2	6		4035			
2	10		6214			
3	1.5		2028			
3	2.5		3158			
3	4		4580			
3	6		5770			
3	10		8877			



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
CORE	2	0.5	67	0.75	76	1	87	1.5	105	2.5	143
CORE	3	0.5	77	0.75	90	1	114	1.5	133	2.5	181
CORE	4	0.5	89	0.75	114	1	133	1.5	152	2.5	228
CORE	5	0.5	105	0.75	124	1	152	1.5	181	2.5	266
CORE	6	0.5	114	0.75	143	1	171	1.5	209	2.5	314
CORE	7	0.5	124	0.75	152	1	181	1.5	238	2.5	352
CORE	8	0.5	143	0.75	171	1	200	1.5	266	2.5	390
CORE	10	0.5	162	0.75	200	1	257	1.5	314	2.5	475
CORE	12	0.5	181	0.75	228	1	285	1.5	371	2.5	570
CORE	14	0.5	200	0.75	257	1	323	1.5	418	2.5	637
CORE	16	0.5	228	0.75	285	1	361	1.5	475	2.5	722
CORE	19	0.5	257	0.75	323	1	418	1.5	542	2.5	827
CORE	24	0.5	304	0.75	399	1	513	1.5	675	2.5	1036
PAIR	1	0.5	67	0.75	77	1	86	1.5	105	2.5	143
PAIR	2	0.5	105	0.75	124	1	143	1.5	171	2.5	238
PAIR	3	0.5	124	0.75	143	1	171	1.5	219	2.5	323
PAIR	4	0.5	143	0.75	171	1	219	1.5	276	2.5	399
PAIR	5	0.5	162	0.75	200	1	257	1.5	333	2.5	485
PAIR	6	0.5	181	0.75	238	1	295	1.5	380	2.5	570
PAIR	7	0.5	200	0.75	266	1	333	1.5	428	2.5	646
PAIR	8	0.5	238	0.75	295	1	380	1.5	494	2.5	741
PAIR	10	0.5	276	0.75	361	1	456	1.5	589	2.5	903
PAIR	12	0.5	314	0.75	409	1	523	1.5	694	2.5	1046
PAIR	14	0.5	352	0.75	466	1	599	1.5	789	2.5	1207
PAIR	16	0.5	399	0.75	523	1	665	1.5	894	2.5	1378
PAIR	19	0.5	447	0.75	608	1	789	1.5	1036	2.5	1597
PAIR	24	0.5	551	0.75	751	1	970	1.5	1302	2.5	2006
TRIAD	1	0.5	79	0.75	95	1	114	1.5	133	2.5	181
QUAD	1	0.5	90	0.75	114	1	133	1.5	152	2.5	219



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	1	0.5	39	0.75	48	1	57	1.5	68	2.5	95
PAIR	2	0.5	61	0.75	77	1	95	1.5	133	2.5	181
PAIR	3	0.5	80	0.75	105	1	133	1.5	171	2.5	257
PAIR	4	0.5	95	0.75	133	1	171	1.5	219	2.5	333
PAIR	5	0.5	124	0.75	162	1	238	1.5	266	2.5	409
PAIR	6	0.5	143	0.75	181	1	256	1.5	323	2.5	485
PAIR	7	0.5	152	0.75	209	1	266	1.5	361	2.5	561
PAIR	8	0.5	171	0.75	228	1	314	1.5	409	2.5	637
PAIR	10	0.5	209	0.75	295	1	380	1.5	513	2.5	799
PAIR	12	0.5	247	0.75	342	1	447	1.5	608	2.5	941
PAIR	14	0.5	276	0.75	390	1	513	1.5	694	2.5	1084
PAIR	16	0.5	323	0.75	437	1	589	1.5	799	2.5	1236
PAIR	19	0.5	371	0.75	523	1	684	1.5	932	2.5	1454
PAIR	24	0.5	456	0.75	646	1	856	1.5	1169	2.5	1844
TRIAD	1	0.5	48	0.75	60	1	73	1.5	93	2.5	143
QUAD	1	0.5	57	0.75	71	1	91	1.5	124	2.5	181

**POLYCAB WIRES PVT. LTD.**

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	124	0.75	143	1	162	1.5	190	2.5	247
PAIR	3	0.5	152	0.75	171	1	200	1.5	247	2.5	342
PAIR	4	0.5	181	0.75	209	1	247	1.5	304	2.5	428
PAIR	5	0.5	219	0.75	257	1	304	1.5	361	2.5	513
PAIR	6	0.5	247	0.75	295	1	352	1.5	428	2.5	608
PAIR	7	0.5	276	0.75	323	1	390	1.5	475	2.5	694
PAIR	8	0.5	304	0.75	371	1	447	1.5	551	2.5	780
PAIR	10	0.5	371	0.75	447	1	542	1.5	675	2.5	970
PAIR	12	0.5	428	0.75	513	1	627	1.5	780	2.5	1141
PAIR	14	0.5	485	0.75	589	1	722	1.5	894	2.5	1302
PAIR	16	0.5	542	0.75	665	1	808	1.5	1008	2.5	1483
PAIR	19	0.5	618	0.75	761	1	941	1.5	1179	2.5	1740
PAIR	24	0.5	780	0.75	951	1	1179	1.5	1492	2.5	2186



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIEDED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr	Size	Rate / mtr
PAIR	2	0.5	82	0.75	95	1	114	1.5	143	2.5	200
PAIR	3	0.5	105	0.75	133	1	162	1.5	200	2.5	285
PAIR	4	0.5	133	0.75	162	1	200	1.5	257	2.5	371
PAIR	5	0.5	162	0.75	200	1	247	1.5	314	2.5	456
PAIR	6	0.5	190	0.75	238	1	295	1.5	371	2.5	542
PAIR	7	0.5	219	0.75	266	1	333	1.5	418	2.5	618
PAIR	8	0.5	247	0.75	304	1	380	1.5	485	2.5	713
PAIR	10	0.5	304	0.75	380	1	475	1.5	599	2.5	875
PAIR	12	0.5	352	0.75	447	1	551	1.5	703	2.5	1046
PAIR	14	0.5	418	0.75	513	1	646	1.5	818	2.5	1207
PAIR	16	0.5	466	0.75	580	1	722	1.5	932	2.5	1378
PAIR	19	0.5	542	0.75	684	1	856	1.5	1093	2.5	1626
PAIR	24	0.5	684	0.75	856	1	1074	1.5	1378	2.5	2044

**POLYCAB WIRES PVT. LTD.****POLYCAB**

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB RUBBER CABLES**ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED , PC TAPE , PCP OUTERSHEATHED ELASTOMERIC RUBBER CABLE (Rate Per Mtr)**

Size Sq.mm	1 Core	2 Core	3 Core	4 Core
1.5	63	164	188	237
2.5	85	218	258	329
4	118	311	367	471
6	187	471	567	758
10	280	714	865	1128
16	401	1001	1250	1633
25	595	--	1922	2492
35	800	--	2535	3300
50	1033	--	3252	4242
70	1536	--	4787	6293
95	2033	--	6345	8323
120	2514	--	7795	10267
150	3082	--	9543	12577
185	3774	--	11676	15428
240	4850	--	15097	19956
300	6022	--	18890	24977
	6 Core	7 Core	8 Core	10 Core
1.5	323	400	484	607
2.5	488	593	693	828
	12 Core	16 Core	19 Core	
1.5	696	901	1061	
2.5	986	1261	1519	



POLYCAB WIRES PVT. LTD.

LDC List Price No. 05/2015-16 effective 1st Sept 2015

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	55	91	162	361	713	1426

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMoured POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	105	143	219	456	808	1521